

Precision pocket thermometer with probe



GTH 175 PT-T

HIGH ACCURACY
AND PRECISION

LIQUIDS
AIR / GAS

SOFT MEDIA

CORE TEMPERATURE
Ø 3 MM

CORE TEMPERATURE
Ø 1.5 MM

NEW

GTH 175 PT-T

GTH 175 PT-E

GTH 175 PT-K

GTH 175 PT-G

GTH 175 PT-T

Temperature measuring device incl. universal probe

GTH 175 PT-E

Temperature measuring device incl. insertion probe

GTH 175 PT-K

Temperature measuring device incl. Teflon insertion probe

GTH 175 PT-G

Temperature measuring device incl. mini Teflon probe

Application:

Accurate measurements in liquids, as core measuring device (with insertion probe), for air/gas measurements or as reference device for multiple times more expensive measuring systems. Handle and cable are resistant to temperatures up to 100 °C.

Options:**- WD**

Probe design: water-proof
Probe as for GTH 175 PT-T and GTH 175 PT-E, but with PVC cable (max. 100 °C) and sealed handle (max. 70 °C).
(Not possible for GTH 175 PT-K and GTH 175 PT-G.)

Special designs upon request:

e.g. longer cable or probe tube.

Accessories and spare parts:**GB 9 V**

Spare battery

GKK 1100

Case (340 x 275 x 83 mm) with foam lining

Full set offer: Device incl. calibration certificate and case, see page 6

Specifications:

Measuring range:	-199.9 ... +199.9 °C
Resolution:	0.1 °C
Accuracy: (at nominal temperature)	0.1 % of meas. value ±2 digit (at range: -70.0 ... +199.9 °C). Probe and device are calibrated together, resulting in an error of about 0.1 °C ±1 digit in range 0 ... 100 °C.
Probe:	All probes are permanently connected to device.
GTH 175 PT-T	Pt1000, 2-wire, volt-free in V4A tube 3 mm Ø and 100 mm long, plastic handle approx. 135 mm long, kink protection and approx. 1 m highly flexible silicone cable
GTH 175 PT-E	Probe (V4A, Ø 3 mm x 100 mm) as above, but additional slim insertion tip for all soft media. Handle and cable are resistant to temperatures up to 100 °C.
GTH 175 PT-K	Probe (V4A, Ø 3 mm x 100 mm) as above, but with Teflon handle and 1 m Teflon cable. Handle and cable are resistant to air temperatures up to 250 °C.
GTH 175 PT-G	Probe (V4A, Ø 1.5 mm x 100 mm) as above, but with Teflon handle and 1 m Teflon cable. Handle and cable are resistant to air temperatures up to 250 °C.
Display:	3½-digit, 13 mm high LCD display
Nominal temperature:	+25 °C
Working temperature:	-30 ... +45 °C
Storage temperature:	-30 ... +70 °C
Power supply:	9 V battery, type IEC 6F22
Battery life time:	approx. 200 operating hours
Battery change indicator:	„BAT“
Dimensions (device):	approx. 106 x 67 x 30 mm (H x W x D). Housing made of impact-resistant ABS.
Weight:	approx. 190 g (incl. battery and probe)